



BENJAMIN MOORE® SUPER SPEC® INTERIOR LATEX FLAT FINISH 275

Features

- Excellent hiding
- Great touch up
- Spatter resistant
- Decorative and uniform flat finish
- Painted surfaces can be washed after one week
- Washable
- Quick dry
- Low odor
- Easy application
- Soap and water clean up.

Recommended For:

For new or previously painted interior wallboard, plaster, masonry and primed or previously painted wood or metal.

General Properties

An acrylic blended latex flat enamel designed for application to a wide variety of interior surfaces and limited exterior surfaces

Limitations:

- White and ready-made colors also suitable for limited exterior use. Benjamin Moore® Color Preview® bases are for interior use only
- Exterior use is limited to properly cured stucco and masonry surfaces
- Do not apply when air and surface temperatures are below 50° F (10° C)

Product Information

Colors — Standard:

275 01 White

A selection of off-whites is also available in limited areas. (White and off-whites may be tinted with up to 2.0 fl. oz. of Benjamin Moore® Color Preview® colorants per gallon.)

— Tint Bases:

Benjamin Moore® Color Preview® Bases 1B, 2B, 3B, & 4B

— Special Colors:

Contact your Benjamin Moore & Co. representative

Certification:

Master Painters Institute MPI #53

Class A (0-25) over non-combustible surfaces when tested in accordance with ASTM E-84

Available in all regulated areas.

Qualifies for
LEED®
Credit
(INTERIOR FLAT)

Federal Specifications Generic Equivalent:

TT-P-29-J

Technical Assistance

Available through your local authorized independent BENJAMIN MOORE® retailer. For the location of the retailer nearest you, call 1-800-826-2623, see www.benjaminmoore.com, or consult your local Yellow Pages.

Technical Data[◇]

Technical Data [◇]		Pastel Base
Vehicle Type	Acrylic Blended Latex	
Pigment Type	Titanium Dioxide	
Volume Solids	32 %	
Theoretical Coverage at Recommended Film Thickness	400 - 450 Sq. Ft.	
Be sure to estimate the right amount of paint for the job. This will ensure proper coverage and minimize the disposal of excess paint.		
Recommended Film Thickness	— Wet	3.8 mils
	— Dry	1.2 mils
Dry Time @ 77° F (25° C) @ 50% RH	— Set To Touch	1 Hour
	— To Recoat	2-3 Hours
	— To Hard Dry	8 Hours
Dries By	Coalescence	
Viscosity	93 ± 3 KU	
Sheen / Gloss	Flat	
Surface Temperature at application	— Min.	50° F
	— Max.	90° F
Thin With	Clean Water	
Clean Up Thinner	Clean Water	
Weight Per Gallon	11.2 lbs.	
Storage Temperature	— Min.	40° F
	— Max.	90° F

Volatile Organic Compounds (VOC)

◇ 46 grams / Liter .38 LBS / Gallon

[◇]Reported values are for Pastel Base.
Contact Benjamin Moore & Co. For values of other bases or colors.

Super Spec® Interior Latex Flat (275)

Surface Preparation

Surfaces must be clean, dry, and free of wax, grease, dust, mildew, and scaling paint. Glossy areas should be dulled. New plaster and masonry must be thoroughly cured before painting.

Exterior: Loose, sandy masonry and stucco should be dry brushed down to a firm surface. Chalk must be removed by use of power wash equipment or by wire brushing. Remove old exterior cement-based paint by sand-blasting. If mildew is evident it must be removed by application of commercial mildew wash. CAUTION: Follow manufacturer's application and safety directions.

Difficult Substrates: Benjamin Moore & Co. offers a number of specialty primers for use over difficult substrates such as bleeding woods, grease, crayon markings, hard glossy surfaces, galvanized metal, or other substrates where paint adhesion or stain suppression is a particular problem. Your BENJAMIN MOORE® retailer can recommend the right problem-solving primer for your special needs.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Primer/Finish Systems

For best hiding results, tint the primer to the approximate shade of the finish coat. **Special Note:** Certain custom colors require a Deep Color Base Primer tinted to a special prescription formula to achieve the desired color. Consult your retailer. No primer is required on most new or previously painted surfaces in good condition. Surfaces in good condition, require only 1 or 2 coats Super Spec® Interior Latex Flat (275).

Previously Painted Surfaces and Wallboard:

Spot prime before and after filling in nail holes, cracks, and other surface imperfections.

Primer: Super Spec® Latex Enamel Undercoater & Primer Sealer (253) where a two coat system is indicated.

Finish: 1 or 2 coats Super Spec® Interior Latex Flat (275).

Unpainted Wood and Unpainted Cured Plaster or Masonry:

Primer: Super Spec® Latex Enamel Undercoater & Primer Sealer (253) or Super Spec® Alkyd Enamel Undercoater & Primer Sealer (C245).

Finish: 1 or 2 coats Super Spec® Interior Latex Flat (275).

Exterior Weathered, Unpainted Masonry:

Primer: Moore's® Alkyd Masonry Sealer (C077) or Moore's® Acrylic Masonry Sealer (066).

Finish: 1 or 2 coats Super Spec® Interior Latex Flat (275).

Rough or Pitted Masonry:

Primer: Super Spec® Latex Block Filler (160).

Finish: 1 or 2 coats Super Spec® Interior Latex Flat (275).

Smooth Poured or Precast Concrete:

Primer: Moore's® Acrylic Masonry Sealer (066) or Super Spec® Latex Enamel Undercoater & Primer Sealer (253).

Finish: 1 or 2 coats Super Spec® Interior Latex Flat (275) Super Spec® Interior Latex Flat (275).

Application

Stir thoroughly before use. Apply one or two coats. For best results, use a Benjamin Moore® Professional custom-blended nylon/polyester brush, Benjamin Moore® Professional roller, or a similar product. This product can also be sprayed.

Spray, Conventional: See **Thinning/Cleanup**

Spray, Airless: Fluid Pressure — 1,500 to 3,000 PSI;
Tip — .013-.017 Orifice

Thinning

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents.

Clean Up

Clean brushes, rollers and other painting tools in warm soapy water after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental, Health & Safety Information

Contains: Crystalline Silica that can cause cancer when in the respirable form (spray mist or sanding dust).

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

FIRST AID: In case of eye contact, flush with water for 15 minutes; for skin, wash with soap and water. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL — Absorb with inert material and dispose of as specified under "Clean Up".

KEEP OUT OF REACH OF CHILDREN

PROTECT FROM FREEZING

Refer to Material Safety Data Sheet for additional health and safety information.

